

INDUSTRIAL AIR COMPRESSORS



DIRECT DRIVE 2.5HP 50LTR CONSTRUCTION FAD 175L/MIN

Cylinders: Single
Power Source: 240V (10 AMP)
Max Pressure: 145 PSI (10 Bar)
Pump Displacement: 218 L/min (7.7 CFM)
Free Air Delivery: 175 L/min (6.2 CFM)
Pump RPM: 2900
Filter / Regulator: Yes
TM350-25050

\$450.00 EXCLUDING GST

\$495.00 INCLUDING GST



BELT DRIVE 2.5HP 90LTR FAD 257L/MIN

Cylinders: V Twin
Power Source: 240V (10 AMP)
Max Pressure: 145 PSI (10 Bar)
Pump Displacement: 318 L/min (11.2 CFM)
Free Air Delivery: 257 L/min (9.1 CFM)
Pump RPM: 1040
Filter / Regulator: Yes
TM351-25090

\$905.00 EXCLUDING GST

\$995.50 INCLUDING GST



BELT DRIVE 3.0HP 60LTR FAD 328L/MIN

Cylinders: Triple
Power Source: 240V (15 AMP)
Max Pressure: 145 PSI (10 Bar)
Pump Displacement: 452 L/min (16 CFM)
Free Air Delivery: 328 L/min (11.6 CFM)
Pump RPM: 945
Filter / Regulator: Yes
TM351-30060

\$994.00 EXCLUDING GST

\$1093.40 INCLUDING GST



BELT DRIVE 3.0HP 90LTR FAD 328L/MIN

Cylinders: Triple
Power Source: 240V (15 AMP)
Max Pressure: 145 PSI (10 Bar)
Pump Displacement: 452 L/min (16 CFM)
Free Air Delivery: 328 L/min (11.6 CFM)
Pump RPM: 945
Filter / Regulator: Yes
TM351-30090

\$1084.00 EXCLUDING GST

\$1192.40 INCLUDING GST

Valid until 31st January 2021 while stocks last. Freight charges apply where applicable, errors & omissions excepted

www.heatleys.com.au



CANNING VALE 50 Vinnicombe Drive T: 08 9256 5200 E: sales@heatleys.com.au

BASSEDEAN Unit 1 / 16 Dyer Road T: 08 6363 7373

KALGOORLIE 149 Boulder Road T: 08 9091 0900

BUNBURY 53 McCombe Road T: 08 9724 2300

WINGFIELD SA 8 Lafitte Road T: 08 7221 7221

CHOOSING THE RIGHT COMPRESSOR

This selection guide shows which models will run particular air tools and is a guide to assist with the selection of the right compressor to suit your needs. It is good practise to allow for a 10-20% increase in the air requirement/consumption of some air tools as the advertised usage is the average and isn't the total L/min under load.

Ideally to maximise a compressors operational life, its duty cycle over any given period should be no more than 60%. If you plan on using high volume air tools for continuous use, you should consider upgrading to a compressor with a higher FAD rating and larger tank capacity to help reduce the load on the compressor and risk of damage.

Model	TM354-25036	TM354-22050	TM350-25050	TM351-22050	2.5HP Construction Series	3 HP Single Cylinder	3 HP Triple Cylinder	5.5HP Petrol	Construction Series Stationary
Nail Gun	✓	✓	✓	✓	✓	✓	✓	✓	✓
Tyre Inflator	✓	✓	✓	✓	✓	✓	✓	✓	✓
Spray Gun – Low pressure	✓	✓	✓	✓	✓	✓	✓	✓	✓
Spray Gun – High pressure	✓	✓	✓	✓	✓	✓	✓	✓	✓
Grease / Caulking gun	✓	✓	✓	✓	✓	✓	✓	✓	✓
Riveters	✓	✓	✓	✓	✓	✓	✓	✓	✓
Belt Sander	✗	✗	✗	●	●	✓	✓	✓	✓
Air Drill	✗	✗	✗	✗	●	✓	✓	✓	✓
Die Grinder	✗	✗	✗	✗	●	✓	✓	✓	✓
Cut Off Tools	✗	✗	✗	✗	●	✓	✓	✓	✓
Air Hammer	✗	✗	✗	●	●	✓	✓	✓	✓
Needle Scaler	✗	✗	✗	✗	✓	✓	✓	✓	✓
Angle Grinder 4" – 5"	✗	✗	✗	✗	✗	✓	✓	✓	✓
Angle Grinder 6" +	✗	✗	✗	✗	✗	✓	✓	✓	✓
Sanders & Polishers	✗	✗	✗	✗	✓	✓	✓	✓	✓
1/2" Ratchet Wrench	●	●	●	●	✓	✓	✓	✓	✓
1/2" Impact Wrench	●	●	●	●	✓	✓	✓	✓	✓
3/4" Impact Wrench	✗	✗	✗	●	●	✓	✓	✓	✓
1" Impact Wrench	✗	✗	✗	✗	✗	✓	✓	✓	✓

✓ Suitable

✗ Not Suitable

● Intermittent Use